

SAP Ariba

Feature at a glance Item Specification field for specifying additional catalog item attributes

Dan Schunk, SAP Ariba Target GA: February, 2019

CONFIDENTIAL



Feature at a Glance

Introducing: Item Specification field for specifying additional catalog item attributes

Customer challenge

An item in the catalog could have additional attributes to describe and identify it, today there is no way to capture these attributes and display them in the Catalog.

Meet that challenge with SAP Ariba

This feature introduces a new Item Spec catalog field to specify the additional attributes or specifications of an item that help describe and identify the catalog item better.

Experience key benefits

Introduce a new field in the Catalog to capture these additional attributes and display them in the catalog. These attributes are also searchable.

Solution area

SAP Ariba Buying and Invoicing SAP Ariba Buying SAP Ariba Catalog

Implementation information

This feature is "on" by default. No action is required to utilize this feature.

Prerequisites and Limitations

None

Feature at a Glance

Introducing: Item Specification field for specifying additional catalog item attributes

CIF Format Information

Element/Attribute	Notes
Item Spec	Format for this field will be {"key1" = "value1"; "key2" = "value2";}

CIF Format Example

Item Spec

```
{"Type of Connection" =
"Flanged";"Mat Body" = "Carbon
Steel";}
```

Feature at a Glance

Introducing: Item Specification field for specifying additional catalog item attributes

Information from Manufacturer: Additional Specifications	A new area will appear in the item details containing all of the new additional specifications	
Mat spec, gland flange	ASTM A105 NORMALISED; ASTM A216 GRADE WCB; ASTM A216 GRADE WCC; ASTM A29 GRADE 4140; ASTM A350 GRADE LF2, CLASS 1; ASTM A352 GRADE LCC	
Mat spec, spring(s)	ASTM B637 UNS N07718	
Nominal size	DN 80	
Type of end connection	FLANGED	
Service(s)	SOUR	
Mat requirement, sour service	NACE MR-01-75 (VERSION 2002)	
Mat spec, dynamic primary seal	FILLED PTFE; MODIFIED PTFE; VIRGIN PTFE	
Tec classification code	BA-TR-SE-BD-SB-BB-XX-I14313-ST	
Type of construction	TWO/THREE PIECE	
Mat spec, stem ASTM A105 NORMALISED; ASTM A182 GRADE F 316; ASTM A182 GRADE F 316L; ASTM A182 GRADE F 6A; ASTM A276 TYPE 316; ASTM A276 TYPE 316L; ASTM A29 GRADE 4140; ASTM A350 GRADE LF2, CLASS 1; ASTM A564 TYPE 630; ASTM A705 TYPE 630		
Additional requirements MESC SPE 77/130 2013; MESC SPE 77/300A 2013; MESC SPE 77/302 2013; MESC SPE 77/312 2012; MESC SPE 77/315 2006; MESC SPE 85/112 2013; MESC SPE 85/203 2012; MESC SPE 85/301 2012		
Mat, body	CARBON STEEL	
Mat spec, seat ASTM A182 GRADE F 316; ASTM A182 GRADE F 316L; ASTM A182 GRADE F 6A; ASTM A276 TYPE 316; ASTM A276 TYPE 316L; ASTM A351 - CF3M; ASTM A351 - CF8M; ASTM A705 TYPE 630		
Mat, seals ELASTOMERIC; GRAPHITE		
Mat spec, seat insert	ec, seat insert NYLON POLY AMIDE (PA) 12/G	
Type of closure member	TRUNNION MOUNTED BALL	
Mat, trim	AISI 316	
Mat spec, closure member	t spec, closure member ASTM A182 GRADE F 316; ASTM A182 GRADE F 316L; ASTM A182 GRADE F 6A; ASTM A351 -CF3M; ASTM A351 -CF8M; ASTM A705 TYPE 630	
Design spec	API SPEC 6D; ISO 14313	
Tune of local		